

## 2018 Bone Stock 3 day build Compact Gasconade County Fair

ANY QUESTIONS CONTACT JOSHUA WAGNER 573-789-5418 OR DANNY BERRY 573-578-8811

- 106" wheel base or less cars allowed in this class and that is factory measurement. Not measured from altering the car
- 4 CYINDER AND 6 CYLINDER CARS ONLY NO TRUCKS OR SUVS
- ABSOLUTELY NO DRIVERS DOOR HITS OR YOU WILL BE DISQUALIFIED
- CAR MUST HAVE WORKING BRAKES
- MUST BE 16 YEARS OF AGE TO DRIVE IN CAR
- MUST WEAR SEAT BELT
- YOU MAY RUN VALVE STEM PROTECTORS ON TIRES THAT IS IT. DOT TIRES ONLY
- ABSOLUTELY NO WELDING ON THIS CAR, IF ANY IS FOUND YOU WILL NOT RUN.
- THIS IS A BONESTOCK CLASS SO BONESTOCK EVERYTHING

1. All trash and loose items must be cleaned out from inside of car
2. All glass must be removed and cleaned out including the headlights and the taillights
3. Battery must be moved to the passenger floor board area
4. Gas tank must be removed and moved to the back-seat area, unless the stock factory gas tank is located in front of the rear axle. If the stock fuel tank is located under the car and in front of the rear axle it may stay in the factory location.
5. All cars must have bright numbers painted on the doors

### BUMPER

You will run the stock bumper that came on the car. You may chain bumper around core support with 2 pieces of chains ( 1 loop ) 3/8" chain . All plastic bumper covers must be removed. This rule applies for the rear bumper as well. If you choose you do not have to run a rear bumper

### HOOD

You are allowed ( 4 ) places of either #9 wire (2 loops ) or 3/8" chain ( 1 loop ) to hold your hood down. You must have a 12 x 12 hole cut in the hood in case of a fire. Hood must be off for inspection.

### **FRONT WINDOW BAR**

You must have piece of 3/8" chain from your roof to your firewall. This can only lap over your roof 4" and also lap over your firewall 4". No welding it must be bolted in with 1 3/8" bolt per side

### **DOORS**

You will allowed 3 spots per door to tie the door shut. You may use either of the next 2 methods, but can only choose 1: first method is #9 wire ( 2 loops ) per spot , second method is 3/8" chain ( 1 loop ) held with a 3/8" bolt

### **TRUNK**

You are allowed ( 4 ) places of either #9 wire ( 2 loops ) or 3/8" chain ( 1 loop ) to hold your trunk down. You must have a 8 x 8 inspection hole in your trunk. Trunk must be in factory location. No V-ing or Tucking allowed.

### **CAGE**

This is a bone stock class. Dash must remain in car. I also will not take away from safety. You must have a seat bar behind seat, on each end of the seat bar must be a 6x6 plate so the seat bar does not poke out of the door from a hit. That plate can be bolted through the outside of the door. Your rollover bar can be built off it. Your rollover bar can be maximum of 2x2 square tubing and it can be bolted to your roof with 2 3/8" bolts .